

CP- UNC-TE13FL3-M**1.3 MP HD IP IR Bullet Camera - 30Mtr.****Main Features**

- 1/3" 1.3Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 30 Mtrs.
- 2.8~12mm varifocal lens
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMs Pro, vOptimus Pro



CP-UNC-TE13FL3-M

1.3 MP HD IP IR Bullet Camera - 30Mtr.

Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control(AGC)
S/N Ratio
Back Light Compensation
Video Compression
Video Streaming
Resolution
Privacy Mask
ICR
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
Interface
Protocol
Ethernet
User Account
IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Regulatory

Specification

1/3" 1.3Megapixel CMOS
0.01Lux/F1.2 (Color), 0.005Lux/F1.2(B/W);0Lux/F1.2(IR on)
Auto/Manual, 1/3(4)~1/10000s
Auto
2.8mm~12mm
Auto/Manual
More than 50 dB
BLC / HLC / DWDR
H.264/MJPEG
Main Stream:1.3M/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
1.3M(1280×960) /720P(1280×720) /D1(704×576) / CIF(352×288)
Up to 4 areas
Auto(ICR)/Color/B/W
1 Ch.
1 Ch.
G.711a / G.711u / PCM
2 Ch.
1 Ch.
1 RS485, 1 RJ45
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
RJ-45 (10/100Base-T)
10 users
IR Range of 30 Mtr.
iPhone, iPad, Android, Windows Phone
Micro SD, Max 64GB
-20°C~+60°C(-H: -40°C~+60°C), Less than 95% RH
DC12V (AC24V optional) , PoE (802.3af)
Max 7.5W(AC 24V:Max 11W)
IP66
CE, FCC and RoHS



CP- UNC-TE13FL3-M

1.3 MP HD IP IR Bullet Camera - 30Mtr.

Feature

Dimension

Weight

Specification

φ104×306.7mm

1.25kg



**Product casing and specifications are subject to change without prior notice*