

CP- UNC-TE20L5-M**2 MP Full HD IP IR Bullet Camera - 50 Mtr.****Main Features**

- 1/2.8" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 3.6mm fixed lens (6mm,8mm optional)
- Supports PoE, IP66
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP-UNC-TE20L5-M

2 MP Full HD IP IR Bullet Camera - 50 Mtr.

Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Lens
Gain Control(AGC)
Back Light Compensation
S/N Ratio
Video Compression
Video Streaming
Resolution
Video Output
Privacy Mask
ICR
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
Protocol
Ethernet
User Account
IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Regulatory
Dimension
Weight

Specification

1/2.8" 2 Megapixel CMOS
0.1Lux/F1.2 (Color), 0.01Lux/F1.2(B/W);0Lux/F1.2(IR on)
Auto/Manual, 1/3(4)~1/10000s
Auto/Manual
3.6mm fixed lens (6mm,8mm optional)
Auto/Manual
BLC / HLC / DWDR
More than 50 dB
H.264/MJPEG
Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
1 channel BNC(1.0Vp-p, 75Ω)
Up to 4 areas
Auto(ICR)/Color/B/W
1 Ch.
1 Ch.
G.711a/ G.711u/ PCM
2 Ch.
1 Ch.
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
RJ-45 (10/100Base-T)
20 users
IR Range of 50 Mtr.
iPhone, iPad, Android, Windows Phone
Micro SD, Max 32GB
-20°C~+60°C, Less than 90% RH
DC12V, PoE(802.3af)
<8W
IP66
CE, FCC and RoHS
88mm × 76mm × 200.2mm
0.92kg