


**CP- UNC-TH4K12ZL5-M****4K Full HD IR Bullet Camera - 50Mtr.****Main Features**

- 1/1.7" 12Megapixel progressive scan CMOS
- Max 15fps@12 MP / 25/30fps@4K
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- 4.1mm ~16.4mm motorized lens
- IR Range of 50 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



# CP-UNC-TH4K12ZL5-M

4K Full HD IR Bullet Camera - 50Mtr.



## Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Gain Control(AGC)  
Lens  
S/N Ratio  
Video Compression  
Back Light Compensation  
Resolution  
Frame Rate  
Privacy Mask  
ICR  
Audio Input  
Alarm IN  
Alarm Out  
Protocol  
Smart Detection  
Ethernet  
User Account  
Smart Phone  
IR  
Micro SD  
Operating Temperature  
Power Source  
Power Consumption  
Weatherproof Standard  
Dimension  
Weight

## Specification

1/1.7" 12Megapixel progressive scan CMOS  
0.05Lux/F1.4(Color); 0Lux/F1.4(IR on)  
Auto/Manual, 1/3(4)~1/10000s  
Auto/Sunny/Night/Outdoor/Customized  
Auto/Manual  
4.1mm~16.4mm  
More than 50dB  
H.264/H.264B/H.264H/ MJPEG  
BLC / HLC / DWDR  
12M(4000x3000)/8M(4096x 2160)/8M(3840x 2160)/1080P(1920x 1 080)/720P(1280x 720) / D1(704x 576) /CIF(352x 288  
Main Stream: 12M(1~15fps)/8M(3840x2160) (1~25/30fps), Sub Stream :D1/CIF(1 ~ 25/30fps),Third Stream:1080P/720P/D1(1 ~ 25/30fps)  
Up to 4 areas  
Auto(ICR)/Color/B/W  
1 Channel  
2 Channel  
1 Channel  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour, 802.1x  
Tripwire, Intrusion,Scene change Missing/Abandoned Audio detect  
RJ-45 (10/100Base-T)  
20 Users  
iPhone, iPad, Android, Windows Phone  
IR Range of 50 Mtr.  
Micro SD, Max 128GB  
-30°C~+60°C, Less than 95% RH  
DC12V/AC24V, PoE (802.3at)  
<24W (with IR on, motorized lens working)  
IP67  
272.9mm × 94.3mm × 94.3mm  
0.8kg