

CP- UNC-VD20L3-VMD**2 MP Full HD Network IR Vandal Dome Camera - 30Mtr.****Main Features**

- 1/3" 2Megapixel PS CMOS Image Sensor
- Max 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC
- Smart Detection supported
- 3.6mm fixed lens (2.8mm, 6mm optional)
- IR Range of 30 Mtrs, IP67, IK10, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-VD20L3-VMD

2 MP Full HD Network IR Vandal Dome Camera - 30Mtr.



Feature

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control(AGC)
Lens
Back Light Compensation
Video Compression
S/N Ratio
Video Streaming
Resolution
Privacy Mask
ICR
Audio Input
Audio Compression
Audio Output
Alarm IN
Alarm Out
Protocol
Smart Detection
Ethernet
User Account
IR
Smart Phone
Micro SD
Ingress Protection
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard

Specification

1/3" 2Megapixel progressive scan CMOS
0.01Lux/F2.0 (Color), 0Lux/F2.0(IR on)
Auto/Manual, 1/3(4)~1/100000s
Auto/Manual
Auto/Manual
3.6mm (2.8mm, 6mm optional)
BLC / HLC / DWDR
H.264/H.264B/H.264H/ MJPEG
More than 50dB
Main Stream: 1080P/720P(1~25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps), Third Stream: 720P(1~13/4fps)
1080(1920×1080) / 720P(1280×720) / D1(704×576/704×480) /CIF(352×288/352×240)
Up to 4 areas
Auto(ICR)/Color/B/W
1 Channel
G.711a / G.711u
1 Channel
1 Channel
1 Channel
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour
Tripwire, Intrusion, Scene Change, Face detect
RJ-45 (10/100Base-T)
20 Users
IR Range of 30 Mtr.
iPhone, iPad, Android, Windows Phone
Max 128GB
IP67
-40°C~+60°C, Less than 95% RH
DC12V, PoE (802.3af)
<4W
IP67 & IK10

 CP- UNC-VD20L3-VMD

2 MP Full HD Network IR Vandal Dome Camera - 30Mtr.

**Feature**

Dimension

Weight

Specification

Φ110mm × 81mm

0.33kg(with package 0.47kg)