

CP- UNR-4K4328**32 Ch. H.265 4K Network Video Recorder****Main Features**

- Up to 32 channel IP camera input
- Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view
- H.265/H.264/MJPEG dual codec decoding
- Up to 12Mp resolution preview and playback
- Max 256Mbps incoming bandwidth
- Support 8 SATA HDDs up to 48TB, 34USB(2 USB3.0), 1 eSATA up to 16TB
- 2 HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-4K4328**32 Ch. H.265 4K Network Video Recorder****Feature**

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
Recording Mode
Search Mode

Playback

Backup Mode
Record Interval
Max User Account
Interface Ports
Ethernet
Protocols
Power Supply
Power Consumption

Specification

Dual-core embedded processor
32 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
2 HDMI, 1 VGA
H.265 / H.264 / MJPEG
3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
Max 192 Mbps
1/4/8/9/16
MD Zones: 396(22×18).
Supports
Supports
16 channel
6 channel
iPhone, iPad, Android, Windows Phone
8 SATA ports, up to 48TB, 1 eSATA port
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

USB Device / Internal SATA burner/ Network
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
2 HDMI, 1 VGA, 4 USB2.0, 1 RS485, 1 RS232, 1 RJ45
2 RJ-45 port (10/100M/1000M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
Single, AC 100~240V, 50/60 Hz
18.8W(Without HDD)

 CP- UNR-4K4328**32 Ch. H.265 4K Network Video Recorder****Feature**

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

445mm × 440mm × 95mm

6.6 Kg. (without HDD)