

CP- UNR-7064T16-R**64 Ch. Network Video Recorder****Main Features**

- 64Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 256Mbps incoming bandwidth
- Support 16 SATA HDDs up to 64TB, 1 eSATA up to 16TB, 4 USB2.0
- Support RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software:KVMS, KVMS Pro



CP- UNR-7064T16-R

64 Ch. Network Video Recorder

Feature

Processor
Operating System
IP Camera Input
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Trigger Events
RAID
Recording Mode
Search Mode

Specification

Dual-core embedded processor
Embedded LINUX
64 channel
1 channel Input, 1 channel Output, RCA
GUI
2 HDMI, 1 VGA, 1 TV
H.264 / MJPEG
1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768 & etc.
Max 192 Mbps
1/4/8/9/16/25/36
MD Zones: 396(22x18).
Supports
Supports
16 channel
6 channel
iPhone, iPad, Android, Windows Phone
16 SATA ports up to 64TB, 1 eSATA port
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Raid 0/1/5/6/10
Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

USB Device / eSATA Device / Internal SATA burner/ Network
2 HDMI, 1 VGA, 1TV, 4 USB2.0, 1 RS485, 1 RS232, 2 RJ45
20 users
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
2 RJ-45 port (10/100M/1000M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2
AC 100~240V, 50/60 Hz



CP- UNR-7064T16-R

64 Ch. Network Video Recorder

Feature

Power Consumption

Working Temp

Dimensions

Weight

Specification

75W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

448mm × 490mm × 133mm

10.5kg~11.5kg (without HDD)



**Product casing and specifications are subject to change without prior notice*