

CP- UNC-TB30ZL6-M**3 MP Full HD IR Bullet Camera - 60Mtr.****Main Features**

- 1/3" 3MP PS CMOS Image Sensor
- Max 20fps@3M and 25/30fps@1080P
- H.264 and MJPEG dual-stream encoding
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 2.7 -12mm Motorized Lens
- IR Range of 60 Mtrs, IP67, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMs Pro, vOptimus Pro



CP- UNC-TB30ZL6-M**3 MP Full HD IR Bullet Camera - 60Mtr.****Feature**

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control(AGC)
Lens
Back Light Compensation
Video Compression
S/N Ratio
Video Streaming
Resolution
Privacy Mask
ICR
Protocol
Ethernet
User Account
Smart Phone
IR
Micro SD
Ingress Protection
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

1/3" 3MP Progressive scan CMOS
0.1Lux/F1.4 (Color), 0Lux/F1.4(IR on)
Auto/Manual, 1/3(4)~1/10000s
Auto/Manual
Auto/Manual
2.7 -12 mm Motorized Lens
BLC/ HLC/ DWDR
H.264/ H.264H/ MJPEG
More than 50dB
Main Stream: 3M(1~20fps)/1080P/720P(1~25/30fps), Sub Stream: D1/CIF(1 ~ 25/30fps)
3M(2304x1296) (2048x1536)/1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1
(704x576/704x480)/CIF(352x288/352x240)
Up to 4 areas
Auto(ICR)/Color/B/W
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP,
DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
RJ-45 (10/100Base-T)
20 Users
iPhone, iPad, Android, Windows Phone
IR Range of 60 Mtr.
Max 128GB
IP67
-30°C~+60°C, Less than 95% RH
DC12V/PoE (802.3af)
<8.5W
IP67
72mm × 80mm × 212.8mm
0.65kg