

**CP- UNC-TH20ZL5-MD****2 MP WDR IR Bullet Camera - 50Mtr.****Main Features**

- 1/1.9" 2MP PS CMOS Image Sensor
- Max 50/60fps@1080P
- Support H.264,MJPEG dual codec
- Ultra WDR(120dB), Ultra Defog, ROI, EIS, Smart detection, Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- 4 -8mm Motorized Lens
- IR Range of 50 Mtrs, IP66, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMs Pro, vOptimus Pro



# CP- UNC-TH20ZL5-MD

## 2 MP WDR IR Bullet Camera - 50Mtr.

### Feature

Image Sensor  
Minimum Illumination  
Shutter Speed  
White Balance  
Gain Control(AGC)  
Lens  
S/N Ratio  
Back Light Compensation  
Video Compression  
Video Streaming  
Resolution  
Video Output  
Privacy Mask  
ICR  
Audio Input  
Audio Output  
Audio Compression  
Alarm IN  
Alarm Out

### Specification

1/1.9" 2MP Progressive scan CMOS  
0.002Lux/F1.65 (Color),0Lux/F1.65(IR on)  
Auto/Manual, 1/3(4)~1/10000s  
Auto/Manual  
Auto/Manual  
4-8 mm Motorized Lens  
More than 50dB  
BLC/ HLC/ WDR(120dB)  
H.264/MJPEG  
Main Stream:1080P/720P(1 ~ 50/60fps), Extra Stream: D1/CIF(1 ~ 50/60fps), Third Stream: 1080P/720P/D1(1 ~ 25/30fps)  
1080P(1920× 1080) / 720P(1280× 720) /D1(704× 576) /CIF(352× 288)  
1 Port  
Up to 4 areas  
Auto(ICR)/Color/B/W  
1 Channel  
1 Channel  
G.711a / G.711u  
1 Channel In  
1 Channel Out  
  
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI  
  
Tripwire, Intrusion, Scene Change, Missing/Abandoned, Audio detect, Face detect  
RJ-45 (10/100Base-T)  
20 Users  
iPhone, iPad, Android, Windows Phone  
IR Range of 50 Mtr.  
Max 64GB  
-30°C~+60°C, Less than 95% RH  
DC12V(AC24V optional), PoE (802.3af)  
Max 12.5W

### Protocol

Smart Detection  
Ethernet  
User Account  
Smart Phone  
IR  
Micro SD  
Operating Temperature  
Power Source  
Power Consumption



# CP- UNC-TH20ZL5-MD

2 MP WDR IR Bullet Camera - 50Mtr.

## Feature

Weatherproof Standard

Dimension

Weight

## Specification

IP66

272.90mm × 94.8mm × 94.8mm

1.25 Kg.



*\*Product casing and specifications are subject to change without prior notice*