

CP- UNC-VE20ZL5-MD**2 MP Full HD WDR IP IR Vandal Dome Camera - 50 Mtr.****Main Features**

- 1/2.7" 2Megapixel PS CMOS Image Sensor
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080P(1920×1080)
- WDR(120dB), Day/Night(ICR), 3D-DNR, AWB, AGC, BLC
- IR Range of 50 Mtrs.
- 2.7mm ~12mm motorized lens
- Supports PoE, IP67, IK10, Micro SD Card
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMs Pro, vOptimus Pro



CP- UNC-VE20ZL5-MD**2 MP Full HD WDR IP IR Vandal Dome Camera - 50 Mtr.****Feature**

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control(AGC)
Lens
S/N Ratio
Back Light Compensation
Video Compression
Video Streaming
Resolution
Privacy Mask
ICR
Audio Input
Audio Output
Audio Compression
Alarm IN
Alarm Out
Protocol
Smart Detection
Ethernet
User Account
IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Regulatory
Dimension
Weight

Specification

1/2.7" 2 Megapixel CMOS
0.01Lux/F1.4(Color); 0Lux/F1.4(IR on)
Auto/Manual, 1/3(4)~1/10000s
Auto/Manual
Auto/Manual
2.7mm~12mm Motorized
More than 50 dB
BLC / HLC / WDR(120dB)
H.264/MJPEG
Main Stream:1080P/720P(1 ~ 25/30fps), Extra Stream: D1/CIF(1 ~ 25/30fps)
1080P(1920×1080)/720P(1280×720)/D1(704×576)/CIF(352×288)
Up to 4 areas
Auto(ICR)/Color/B/W
1 Ch.
1 Ch.
G.711a/ G.711u/ AAC
1 Ch.
1 Ch.
IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour, ONVIF Profile S
Tripwire, Intrusion, Scene Change, Face Detect
RJ-45 (10/100Base-T)
20 users
IR Range of 50 Mtr.
iPhone, iPad, Android, Windows Phone
Micro SD, Max 128GB
-40°C~+60°C, Less than 95% RH
DC12V, PoE(802.3af)
<10W (with IR on, motorized lens working)
IP67 & IK10
CE, FCC and RoHS
Φ159mm × 117.9mm
0.8kg