

CP-UNC-VA13L3-MW**1.3MP HD WiFi IR Vandal Dome Camera - 30Mtr.****Main Features**

- 1/3" 1.3MP PS CMOS Image Sensor
- Max 25/30fps@1.3MP(1280×960)
- H.264 & MJPEG dual-stream encoding
- Wi-Fi support
- DWDR, Day/Night(ICR), Auto Iris, 3DNR, AWB, AGC, BLC
- 3.6mm fixed lens (6mm optional)
- IR Range of 30 Mtrs, IP67, IK10, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS Pro, vOptimus Pro



CP- UNC-VA13L3-MW**1.3MP HD WiFi IR Vandal Dome Camera - 30Mtr.****Feature**

Image Sensor
Minimum Illumination
Shutter Speed
White Balance
Gain Control(AGC)
Lens
Video Compression
S/N Ratio
Back Light Compensation
Video Streaming
Resolution
Privacy Mask
ICR
Wireless

Protocol

Ethernet
User Account
IR
Smart Phone
Micro SD
Operating Temperature
Power Source
Power Consumption
Weatherproof Standard
Dimension
Weight

Specification

1/3" 1.3MP Progressive scan CMOS
0.1Lux/F2.0(Color), 0Lux/F2.0(IR on)
Auto/Manual, 1s~1/100000s
Auto/Manual
Auto/Manual
3.6mm (2.8mm optional)
H.264/H.264H/H.264B/MJPEG
More than 50dB
BLC/ HLC/ DWDR
Main Stream: 1.3MP/720P(1~25/30fps), Extra Stream: D1(1 ~ 25/30fps)
1.3M(1280×960)/720P(1280×720)/D1(704×576/704×480) /CIF(352×288/352×240)
Up to 4 areas
Auto(ICR)/Color/B/W
Wi-Fi(IEEE802.11b/g/n), 50m(open field)

IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP,RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS,Bonjour, ONVIF, PSIA, CGI

RJ-45 (10/100Base-T)
20 Users
IR Range of 30 Mtr.
iPhone, iPad, Android, Windows Phone
Max 128GB
-30°C~+60°C, Less than 95% RH
DC12V, PoE (802.3af)
<4.5W(IR ON)
IP67 & IK10
Φ 110mm × 81mm
0.47kg