

CP- UNR-108F1

8 Ch. Network Video Recorder



Main Features

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 56Mbps incoming bandwidth
- Support 1 SATA HDDs up to 4TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras, Support P2P (QR code Scan)
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-108F1

8 Ch. Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Hard Disk
Smart Phone
Trigger Events
Recording Mode
Search Mode
Playback
Backup Mode
Record Interval
Max User Account
Interface Ports
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

Dual-core embedded processor
8 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
H.264 / MJPEG
1920 x 1080, 1280 x 1024, 1280 x 720, 1024 x 768
Max 56 Mbps
1/4/8/9
MD Zones: 396(22×18).
Supports
Supports
1 SATA ports, up to 4TB
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
USB Device / Internal SATA burner/ Network
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
1 RJ-45 port (10/100M)
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.4
Single, DC5V/2A
<2W (without HDD)
-10 ~+55°C / 10~90%RH / 86~106kpa
Smart Box, 192mm×128mm×36mm
320g (without HDD)