

CP- UNR-4K6128R16**128 Ch. H.264 4K Super Network Video Recorder****Main Features**

- Up to 128 channel IP camera input
- Up to 12Mp resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 16 SATA III ports, up to 96TB, 4 USB(2 USB3.0), 1 eSATA port
- Support iSCSI & Mini SAS to expand storage space
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/6/10/50/60
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, Wcmob
- CMS Software: KVMS, KVMS Pro



CP- UNR-4K6128R16

128 Ch. H.264 4K Super Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
HDD Management

Specification

Dual-core embedded processor
128 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
2 HDMI(up to 3840× 2160), 1 VGA
H.264 / MJPEG
3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
Max 256 Mbps
The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16
MD Zones: 396(22×18).
Supports
Supports
16ch, low level effective, green terminal interface
8ch, Relay contact(1A@24VDC), NO/NC programmable, green terminal interface
16 SATA III ports, up to 96TB, 1 eSATA
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Single, Raid 0/1/5/6/10/50/60 (Support global HDD hot-spare)
Manual, Schedule(Regular(Continuous), MD(Video detection: Motion detection,Camera blank, Video loss), Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
128Mbps in Raid 5 mode, 64Mbps in single HDD mode
USB Device/Network/Internal SATA burner/eSATA Device
2 HDMI, 1 VGA, 4 USB ports(3 USB2.0, 1 USB3.0), 1 Mini SAS port, for storage expansion, 1 RS485, 1 RS232, 2 RJ45
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
2 RJ-45 port (10/100M/1000M), 2 Ethernet ports joint working or 2 independent 1000Mbps Ethernet ports
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,PPPOE, DDNS, FTP, Alarm Server,ONVIF Version 2.4



CP- UNR-4K6128R16

128 Ch. H.264 4K Super Network Video Recorder

Feature

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

AC100V~240V, 50~60Hz

51W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

531.9mm × 485mm(with ears) × 133.2mm

17.45kg (without HDD)



**Product casing and specifications are subject to change without prior notice*