

CP- UNR-4K664R8

64 Ch. H.264 4K Super Network Video Recorder



Main Features

- Up to 64 channel IP camera input
- Up to 12Mp resolution preview and playback
- Max 384Mbps incoming bandwidth
- Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0), 1 eSATA port
- Support iSCSI to expand storage space
- 2 HDMI / 1 VGA simultaneous video output
- Support Multi-brand network cameras
- Support RAID 0/1/5/6/10/50/60
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-4K664R8

64 Ch. H.264 4K Super Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Video Recording
Video Display Split
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Hard Disk
Smart Phone
Trigger Events
HDD Management

Recording Mode

Search Mode
Playback
Backup Mode
Interface Ports
Record Interval
Max User Account

Ethernet

Protocols

Power Supply

Specification

Dual-core embedded processor
64 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
2 HDMI(up to 3840× 2160), 1 VGA
H.264H / H.264 / MJPEG
3840× 2160, 1920× 1080, 1280× 1024, 1280× 720, 1024× 768
Max 256 Mbps
The 1st screen: 1/4/8/9/16/25/36, The 2nd screen: 1/4/8/9/16
MD Zones: 396(22×18).
Supports
Supports
16ch, low level effective, green terminal interface
8ch, Relay contact(1A@24VDC), NO/NC programmable, green terminal interface
8 SATA III ports, up to 48TB, 1 eSATA port
iPhone, iPad, Android, Windows Phone
Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Single, Raid 0/1/5/6/10/50/60 (Support global HDD hot-spare)
Manual, Schedule(Regular(Continuous), MD(Video detection: Motion detection,Camera blank, Video loss), Alarm), Stop
Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
128Mbps in Raid 5 mode, 64Mbps in single HDD mode
USB Device/Network/Internal SATA burner/eSATA Device
2 HDMI, 1 VGA, 4 USB ports(3 USB2.0, 1 USB3.0), 1 RS485, 1 RS232, 2 RJ45
1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
128 users
2 RJ-45 port (10/100M/1000M), 2 Ethernet ports joint working or 2 independent 1000Mbps Ethernet ports
HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,PPPOE, DDNS, FTP, Alarm Server,ONVIF Version 2.4
AC110V~240V, 50~60Hz

 CP- UNR-4K664R8**64 Ch. H.264 4K Super Network Video Recorder****Feature**

Power Consumption

Working Temp

Dimensions

Weight

Specification

40W(without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

486mm × 454.9mm × 91mm

<9kg (without HDD)